

Marche Collection



PRODUCT DETAILS

Product Type	Glue Down LVT
Collection	Marche
Construction	Vinyl Dryback Plank / Vinyl Dryback Tile
Classification	ASTM F1700-Class III, Type A-Smooth, Type B-Embossed
Overall Thickness	2.5 mm (.10")
Wear Layer	22 mil (0.55 mm)
Edge Profile	Micro-bevel
Surface Finish	UV Coating
Embossing	Photo Match Embossing / Stone Embossing
Size	Plank 8" W x 48" L / 203.2 mm x 1219.2 mm Tile 12" W x 24" L / 304.8 mm x 609.6 mm
Square Feet Per Carton	34.6710 sf/ctn; 36 sf/ctn
Pieces Per Carton	13 pieces/ctn; 18 pieces/ctn
Weight Per Carton	29.96 lbs/ctn; 31.24 lbs/ctn
Carton Per Pallet	85 ctns/plt; 72 ctns/plt
Installation Method	Glue Down

TECHNICAL PROPERTY

Dimensional Stability	ASTM F2199 -Passes- ≤ 0.02 " / lineal ft. (305 mm)
Curling	ISO 23999 - Passes - ≤ 2 mm
Static Load	ASTM F970 -Passes- ≤ 0.005 " (0.13mm)
Flexibility	ASTM F137 -Passes- 1" mandrel passed
Residual Indentation	ASTM F1914 -Passes- Avg $\leq 8\%$, Max 10%
Resistance to Chemicals	ASTM F925 -Passes- No more than "Slight Change"
Critical Radiant Flux	ASTM E648 -Passes- Class I: ≥ 0.45 W/Sq.cm
VOCs/TVOCs	CDPH/EHLB -Compliant
Substances of Very High Concern	REACH SVHC 191 -Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 -Passes
Phthalates	ASTM D7823 /CPSC-CH-C1001-09.3 -Passes
Slip Resistance	EN14041 - Result: Class DS
IIC	ASTM E492 & ASTM E989 - Result: 66
STC	ASTM E90 & ASTM E413 - Result: 67

SUSTAINABILITY

Material	Clean Recycle W/O DOTP
Certification	FloorScore® certified


SERVICE

Warranties	Limited Lifetime Warranty
------------	---------------------------





**2301
Bianca**



**2302
Aurora**



**2303
Chiara**



**2305
Viola**



**2306
Marta**



**2307
Sofia**



**2308
Greta**



**2309
Dolce**



**2310
Adona**



**2311
Edda**



**2312
Fia**



**2313
Coco**