

Como+ Collection



2113 Da Vinci



2114 Maronne



2115 Grigio

PRODUCT DETAILS

Product Type	Rigid Engineered Luxury Vinyl
Collection	Como+ Collection
Construction	Solid Vinyl Plank
Classification	ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed
Overall Thickness	5.5mm (0.2165")
Wear Layer	22mil (0.55mm)
Underlayment	1.5mm IXPE (0.0591")
Edge Profile	Micro Bevel
Surface Finish	Ceramic Bead
Embossing	Photo Match Embossing
Edge Profile	Easy-to-install with I4F Locking system
Size	9" W x 60" L (228x1511mm)
Square Feet Per Carton	22.25 SQFT/CTN
Pieces Per Carton	6 PIECES/CTN
Weight Per Carton	17.57 KGS/CTN 38.73 LBS/CTN
Carton Per Pallet	60 CTNS/PLT
Installation Method	Floating/Glue Down

TECHNICAL PROPERTY

Dimensional Stability	ASTM F2199 - Passes - ≤0.2% / lineal ft. (305 mm)
Curling	ISO 23999 - Passes - ≤2mm
Static Load	ASTM F970 - Passes - ≤0.005" (0.13mm) (without underlayer)
Static Load Limit	SIM Test - 1000 psi (0.02mm) (without underlayer)
Residual Indentation	ASTM F1914 - Passes - Average: ≤0.007" (0.18mm) (without underlayer)
Resistance to Chemicals	ASTM F925-Passes-No more than a slight change in surface
Resistance to Heat	ASTM F1514 - Passes - Average ΔE < 8.0
Resistance to Light	ASTM F1515 - Passes - Average ΔE < 8.0
Critical Radiant Flux	ASTM E648 - Passes - Class I: ≥ 0.45 W/Sq.cm
Smoke Density	ASTM E662 - Passes - Flaming & Non Flaming ≤ 450
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method v1.2 Compliant
Substances of Very High Concern	REACH SVHC 191 - Passes - Per Substance: ≤0.1% w/w
Heavy Metals	ASTM F963 - Passes
Phthalates	ASTM D7823 - Passes - CPSC-CH-C1001-09.3
Slip Resistance	ASTM D2047- Dry: 0.38 Wet: 0.90
Fungi Resistance	ASTM G21-15 - Passes
IIC Rating	ASTM E492 & ASTM E989 - Result: 73
STC Rating	ASTM E90 & ASTM E413 - Result: 72

SUSTAINABILITY

Material	Virgin Vinyl
Certification	Floor Score® certified
Environmental Product Declaration	EPD Vinyl Click
Health Product Declaration	HPD 2.1 Vinyl Click - 1000 ppm

SERVICE

Warranties	Limited Lifetime Warranty
------------	---------------------------

