

Certified Lights™

Brass Landscape Pro Spot Light Fixture

Materials

Die-cast brass

BODY


Precision machined from solid brass casting; Enclosed and water resistant wireway.

SHROUD

Precision machined and comes with a factory sealed socket resistant glass lens to prevent water intrusion. Accepts up to one additional lens/hex cell accessory.

LENS

Clear flat glass lens



Certified Lights™

Brass Landscape Spot Light Fixture

Materials

Cast brass.

BODY


Precision machined from solid brass casting; Enclosed and water resistant wireway.

SHROUD

Precision machined and comes with a factory sealed socket resistant glass lens to prevent water intrusion. Accepts up to one additional lens/hex cell accessory.

LENS

Clear convex glass lens



LED MR16 Lamp

5 Watts

60° Beam Angle

Color choices between WW 2700K or CW 6500K

BODY

Corrosion resistant non-metallic canister. Fully potted wire cavity provides water-tight seal. Adjustable lamp gimble for optimal results.

DEBRIS GUARD

Solid cast brass faceplate with grate

Contact us



www.CertifiedLights.com



info@certifiedlights.com



972-512-0000



Certified Lights™ Brass Path & Area Light Fixture

MATERIALS

Solid brass

STEM

Brass unibody design provides enclosed, water resistant wireway

SHROUD

Stamped brass. Reflective powder coat interior.

LED C4 Bi-Pin Lamp

FEATURES

- 2 watts.
- WW 2700K.
- Suitable for damp locations.
- Rated for outdoor use in an enclosed fixture.
- Operating temperature -4°F-122°F
- Dimmable with most magnetic transformer..
- Fully potted electronics.



LT3150/LT3300



LT3600/LT3900

Certified Lights™ In-Ground Landscape Well Light with Lens

BODY

Corrosion resistant non-metallic canister.
Fully potted wire cavity provides water-tight seal.
Adjustable lamp gimble for optimal results.

DEBRIS GUARD

Solid cast brass faceplate with grate

MATERIALS

Die-cast brass,PVC

GASKET

High-temperature silicone o-ring for a water-tight seal

LED PAR36 Lamp

FEATURES

- 13 Watts.
- 60° Beam Angle.
- Suitable for damp locations.
- Overheating protection.
- Rated for outdoor use in an enclosed fixture.
- Operating temperature - 4 deg * F - 122 deg * F.
- Dimmable with most magnetic transformer.
- Fully potted electronics.

150W and 300W

FEATURES

- Quick mount bracket.
- Sealed removable lockable hinged door.
- Pre-scored knockouts sides and bottom panel.
- Tool less removable bottom panel.

Contact us



www.CertifiedLights.com



info@certifiedlights.com



972-512-0000