

SOLID VINYL WALLPAPER CANNOT BE PAINTED.

Cleanup: Clean tools, spills and splatters immediately with soap and water.

KEEP FROM FREEZING - DO NOT THIN



Clean, dull and dry surface



Stir paint thoroughly



Start at ceiling edge



Paint "N" pattern - fill in



Paint trim last



Soap and water clean up

CAUTIONS - CONTAINS CRYSTALLINE SILICA: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection or leave the area. Adequate ventilation required when sending or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If allowed, call Poison Control Center, hospital emergency room, or physician immediately.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE: Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY
KEEP OUT OF THE REACH OF CHILDREN.

Paint & Save®

Premium Paint at Outlet Prices SEMI-GLOSS



Latex Paint

Interior / Exterior

PROTECT FROM
FREEZING

1 Gal.
(124 OZ / 3.667 Lts.)

Where To Use: Walls, cabinets, ceilings, trim and doors. Use over drywall, wood, concrete/brick, plaster and wallpaper. See below for preparation steps.

How Much You Need: For one coat coverage, apply at a maximum of 400 square feet per gallon. Rough or textured surfaces may require more - allow for 125-300 square feet per gallon. Do not thin.

What Tools To Use: May be applied with a quality roller, a nylon/polyester brush, or a paint pad.

How To Apply: Room and surface temperature must be 50 degrees Fahrenheit. Allow at least 4 hours of drying time before recoating. Mix gallons together for color and sheen uniformity when using more than one gallon of the same product.

Care for Freshly Painted Surfaces: Freshly painted surfaced may be washed either 30 days- Until then avoid touching, wiping, or wetting the surface. Then clean with mild, non-abrasive, non-oily cleanser and water. Do not place objects on painted surfaces until thoroughly dry. Soap and Water Cleanup.

HOW TO PREPARE THE SURFACE

Previously Painted Surfaces: Remove loose paint, wash with a mild, non-abrasive, non-oily cleanser and water. Rinse completely, let dry. Patch holes and cracks with speckling paste and let dry. Sand patched area and wipe off residue. Sand all smooth or glossy surfaces, rinse well.

Unpainted Surfaces: Wallboard or Drywall

Concrete/brick: Allow new masonry to cure at least 30 days. Etch smooth unpainted concrete. Remove all loose concrete and efflorescence. Rinse and allow to dry (Plaster (new) - Must be dried and cured for 30 days.

Prime with primer. Let dry 4 hours before top coating.

Wallpaper: Vinyl coated wallpaper may be coated if all seams and edges are glued tight. Self-sand and wipe clean. Use primer and allow 24 hours to dry.

CAS NO.	Ingredients
7732-18-5	Water
Proprietary	Vinyl Polymer
13463-67-7	Titanium Dioxide
Proprietary	Acrylic Polymer
471-34-1	Calcium Carbonate
14464-46-1	Cristoballite
NON-PHOTOCHEMICALLY REACTIVE	