

# CUSTOM FILLED

## DIRECTIONS

1. The surface must be clean, dry and dust-free
2. Shake aerosol for at least two minutes, after the agitator ball is free
3. Apply in cross coats from distance of 250mm from object
4. Drying time: 10 - 20 minutes
5. After use turn aerosol upside down empty valve

## WARNING

Danger. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Buildup of explosive mixtures possible without sufficient ventilation. Product contains: acetone, n-butyl acetate.



520




e3

UK  
CA

2004/42/11B(e),  
VOC max. 840g/l,  
VOC 711.0 g/l

AUTO PAINTS  
UNIT 3 KINGFISHER COURT  
SANDWASH CLOSE  
RAINFORD  
MERSEYSIDE  
WA11 8LY



UFI code: 8JR2-3XQQ-2410-NJ7G

400ml

# CAMOUFLAGAGE