



SITE LEGEND	
	PROPERTY LINE
	RIGHT-OF-WAY
	PROPOSED RIGHT-OF-WAY
	PARKING STALL COUNT
	STRAIGHT CURB
	LIGHT POLE (BY OTHERS)
	FENCE
	PARKING BLOCK
	SIGN
	CONCRETE BOLLARD
	HEAVY DUTY ASPHALT PAVEMENT
	LIGHT DUTY ASPHALT PAVEMENT
	CONCRETE DOCK APRON PAVEMENT
	CONCRETE WALK
	MULTI-USE PATH (PER OFFSITE PLAN)

- SITE LAYOUT NOTES**
- ALL DIMENSIONS AND COORDINATES REFER TO EDGE OF PAVEMENT, FACE OF CURB, AND/OR FACE OF BUILDING WHERE APPLICABLE.
 - ALL CURB AND SIDEWALK RADII SHALL BE 5'-0" UNLESS OTHERWISE NOTED.
 - PROVIDE STRIPING AND SYMBOLS AS SHOWN PER ODOT ITEM 640 AND 641. STRIPING PAINT SHALL BE ODOT ITEM 740.02 TYPE 4 WITHOUT GLASS BEADS. TYPICAL LINE WIDTH SHALL BE 4 INCHES, COLOR WHITE.
 - SAWCUT FULL DEPTH SIDEWALK AND PAVEMENT WHERE NEW WORK ABUTS EXISTING CONSTRUCTION. TAKE CARE TO PROVIDE NEAT STRAIGHT LINES. PROVIDE PAVEMENT SEALANT PER ODOT ITEM 423 AT JOINT BETWEEN EXISTING AND NEW ASPHALT, REMOVE CONCRETE TO NEAREST JOINT. PROVIDE 1/2" PREFORMED EXPANSION JOINT FILLER BETWEEN NEW AND EXISTING CONSTRUCTION.
 - ANY PROPERTY PINS DAMAGED AS PART OF CONSTRUCTION SHALL BE RESET BY AN OHIO REGISTERED SURVEYOR.
 - BUILDING DIMENSIONS AND COORDINATES PROVIDED FOR BUILDING LOCATION ONLY. REFER TO ARCHITECTURAL DRAWINGS FOR BUILDING LAYOUT.
 - PROVIDE HANDICAP ACCESSIBLE PARKING SIGNS AS SHOWN. FINAL LOCATION OF SIGNS TO BE DETERMINED BY ARCHITECT.
 - ALL ADA RAMP CURB SHALL BE FORMED AND NOT SAW-CUT.
 - PROVIDE ISOLATION JOINTS WHERE NEW CONCRETE ABUTS EXISTING AND PROPOSED STRUCTURES OR FIXED OBJECTS.
 - REFER TO ELECTRICAL DRAWINGS FOR ELECTRICAL SITE PLAN LIGHT POLE LAYOUT AND DETAILS.

