



Project:	Date:
Prepared by:	Notes:

# 8 FT LED T8 TUBE by JaMES

## Product Description:

8 foot LED T8 system with external driver. The LED T8 system replaces traditional T8 systems. Comes standard single pin. AC-Direct.



## Common Technical Data:

Color Temperature	2700K to 5000K
CRI	> 80
Operation Temperature	-20°C to 50°C
Input Voltage	AC100-277V
Frequency	50-60Hz
Power Factor	More than 0.99
Rated Life	50,000 hours
Power Supply Efficiency	90%



## Product Specification:

Product code	Length (ft)	Certificate	Input Voltage	Lumens	Description			
				3000K-5000K	CRI	Driver Type	Housing	Wire Input
ZY-T8-31W2400 BONT	8	UL	AC100-277V	3720 lm	>80	Internal	Aluminum	Two End
ZY-T8-40W2400 BONT	8	UL	AC100-277V	4800 lm	>80	Internal	Aluminum	Two End

## Ordering Guide:

ZY	/	T8	/	31W/40W	/	2400	/	B	/	O	/	NT	/	3000K-5000K
Company Code		Housing Type		Wattage		Length		2835 LED		External Driver		Input Type		CCT

## Warranty:

This product has a warranty for a period of 5 years from the date of purchase. The warranty is invalid in the case of improper installation, tampering, or removal of the Q.C. date label. Installation in an improper working environment or installation not according to the current edition of the National Electric Code also invalidates the warranty. Should this product fail during the warranty period, it will be replaced free of charge, subject to correct installation and return of the faulty unit. ALG does not accept responsibility for any installation costs associated with the replacement of this product. This warranty is an addition to the statutory rights in the country of purchase. ALG reserves the right to alter specifications without prior notice.

[www.axisledlights.com](http://www.axisledlights.com)

Contact your Regional Account Manager

Office: 614.633.7955

[contact@axisledlights.com](mailto:contact@axisledlights.com)



**AXIS LED GROUP, LLC**  
**US Regional Office**  
Dublin, OHIO  
**Warehouses Located in:**  
Chicago, Dallas, Detroit,  
El Paso, Los Angeles,  
and Philadelphia