


Add:Changyinsha Industrial Zone, Zhangjiagang

Item	Name	Pictures	Description
L-01	Precision screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange Main Material: S.S.304,316,316L, hastelloy,etc.
L-02	Arc screen		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance clearance ± 0.1 mm Main material: S.S.304,316,316L, hastelloy,etc.
L-03	Circular screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange Main Material: S.S. 304,316L, hastelloy,etc.
L-04	Wedge mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange Main Material: S.S. 304,316L, hastelloy,etc.

L-05	Wedge mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Filter Element Main Material: S.S.304,316,316L, hastelloy,etc.
L-06	Counter roll screen		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Enhances Support Rod Main Material:S.S. 304,316,316L, hastelloy,etc.
L-07	Drainage plate		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance clearance ± 0.1 mm Main material S.S.304,316,316L, hastelloy,etc.
L-08	Precision inclined round type filter		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Filter Element Main Material: S.S. 304,316,316L, hastelloy,etc.
L-09	Squeezing machine filter		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Enhances Support Rod Main Material:S.S. 304,316,316L, hastelloy,etc.

L-10	Backwash filter		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Handle Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-11	Wedge mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Filter Element Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-12	Sift barrel		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Filter Element Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-13	Filter canister		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Filter Element Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-14	Reflexed screen tube		OD: 19mm-1250mm Gap 0.02-8.10mm Length 200-6000mm Tolerance clearance ± 0.1 mm Main material S.S. 304, 316L, hastelloy, etc.

L-15	Filter circular screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance clearance: ± 0.1 mm Main material S.S. 304,316L, hastelloy,etc.
L-16	Screen nozzle		OD: 19mm-1250mm Gap: 0.02-8.10mm Gasket/ Nut Tolerance clearance: ± 0.1 mm Main material S.S. 304,316L, hastelloy,etc.
L-17	Filter circular screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S. 304,316,316L, hastelloy,etc.
L-18	screen mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S,304,316,316L, hastelloy,etc.
L-19	Mixed bed team-record		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S. 304,316,316L, hastelloy,etc.






L-20	Cross tube inlet device		OD 19mm-1250mm Gap 0.02-8.10mm Length 200-6000mm Tolerance clearance: ± 0.1 mm Flange/Main/Branch Pipe Main material S.S. 304,316L, hastelloy,etc.
L-21	V type round wire welding plate		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance clearance ± 0.1 mm Main material: S.S.304,316,316L, hastelloy,etc.
L-22	Gravity sieving slice		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance clearance ± 0.1 mm Main material: S.S.304,316,316L, hastelloy,etc.
L-23	Pressure curve of cascade screen piece		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance clearance ± 0.1 mm Curving 120° Main material S.S.304,316,316L, hastelloy,etc.
L-24	Screen basket		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Handle Main Material: S.S.304,316,316L, hastelloy,etc.

L-25	By outward filter cores		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange Main Material:S.S.304,316,316L, hastelloy,etc.
L-26	Inside walk brush filter cores		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange Main Material: S.S.304,316,316L, hastelloy,etc.
L-27	Wedge mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange / Handle Main Material:S.S.304,316,316L, hastelloy,etc.
L-28	Take strengthen circle filter cores		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange Main Material:S.S.304,316,316L, hastelloy,etc.
L-29	Filter screen		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange Main Material:S.S. 304,316,316L, hastelloy,etc.

L-30	Filter backwash		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange Main Material:S.S.304,316,316L, hastelloy,etc.
L-31	Screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange /Filter Element Main Material:S.S.304,316,316L, hastelloy,etc.
L-32	Screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Flange Main Material:S.S.304,316,316L, hastelloy,etc.
L-33	Reflexed screen		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance:±0.1mm Main Material:S.S.304,316,316L, hastelloy,etc.
L-34	Screen		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance clearance ±0.1mm Main material S.S.304,316,316L, hastelloy,etc.

L-35	Wedge filter		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-36	Reflexed screen		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange/ Handle Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-37	Screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange/Filter Element Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-38	50 microns screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S. 304, 316, 316L, hastelloy, etc.
L-39	Wedge mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S. 304, 316, 316L, hastelloy, etc.

L-40	Reflexed screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange Main Material: S.S. 304,316,316L, hastelloy,etc.
L-41	Anti round tapered screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S. 304,316,316L, hastelloy,etc.
L-42	20 microns screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange Main Material: S.S. 304,316,316L, hastelloy,etc.
L-43	Round filter screen		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material: S.S. 304,316,316L, hastelloy,etc.
L-44	Arc screen		Gap: 0.02-8.10mm Length/Width: 200-6000mm Tolerance Clearance: ± 0.1 mm Main material S.S.304,316,316L, hastelloy,etc.

L-45	Take shaft screen tube		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Filter Element Main Material: S.S,304,316,316L, hastelloy,etc.
L-46	Backwash mesh		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Flange / Enhances Support Rod Main Material: S.S.304,316,316L, hastelloy,etc.
L-47	30 microns backwash screen		OD: 19mm-1250mm Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Main Material:S.S.304,316,316L, hastelloy,etc.
L-48	50 microns of the pressure curved screen plate		Gap: 0.02-8.10mm Length: 200-6000mm Tolerance Clearance: ± 0.1 mm Curing 120° Main Material: S.S. 304,316,316L, hastelloy,etc.
L-49	Super screen		OD: 1050mm Gap: 0.3mm Length: 3000mm Tolerance Clearance: ± 0.1 mm Main Material:S.S.304

L-50	well screen filters		OD: 33mm Gap: 0.4mm Length: 500mm Tolerance Clearance:±0.1mm Main Material:S.S.316L
L-51	slotted filter		OD: 53mm Gap: 0.2mm Length: 600mm Tolerance Clearance:±0.1mm Main Material:S.S.304
L-52	centrifugal basket		Top OD: 530mm Bottom OD: 270mm Gap: 0.2mm Height: 500mm Tolerance Clearance:±0.1mm Main Material:S.S.304

Product specifications can be customized according to users' requirements