

CUT LINE

Please change to "IF"

Please change to "REQUIRING"

Please move the 12 FL OZ (0.355L), MADE IN USA icon, and QR code down to the edge of the blue dotted line

Please move this text down to the edge of the blue dotted line

Please make font size slightly larger



CHALET

HIGH TEMP BRAKE FLUID

DOT 3 LÍQUIDO DE FRENOS PARA ALTAS TEMPERATURAS

FOR ALL ABS, DISC, AND DRUM SYSTEMS REQUIRING DOT 3 FLUIDS
PARA TODOS LOS SISTEMAS DE ABS, DISCO Y TAMBOR QUE REQUIEREN DOT 3 FLUIDOS

12 FL OZ (0.355L) MADE IN USA

WARNING: HARMFUL IF SWALLOWED. EYE IRRITANT. SEE WARNING ON BACK LABEL. ADVERTENCIA: DAÑINO SI SE INGIERE. IRRITANTE DE OJOS. Vea las precauciones en el panel posterior.



CHALET

HIGH TEMP DOT 3 BRAKE FLUID
LÍQUIDO DE FRENOS PARA ALTAS TEMPERATURAS

Chalet High-Temp Brake Fluid DOT 3 is specially formulated for safe and high performance operation of today's modern, high powered vehicles. It is designed for all ABS, disc, or drum brake systems and hydraulic clutches that require DOT 3 fluids, and it provides the following benefits:

- Helps protect against brake failure from vapor lock
- Helps prevent brake system corrosion
- Safety mixes with other brands of DOT 3 brake fluids
- Has a high temperature dry boiling point of 400°F for extended fluid life and extra margin of safety

CHALET HEAVY DUTY BRAKE FLUID DOT 3 SURPASSES FEDERAL MOTOR VEHICLE SAFETY STANDARDS 116, FEDERAL SPECIFICATIONS W-8-660, FMVSS 116 (UNITED STATES), CMVSS 116 (CANADA), AND J-1703 (JAPANESE) BOILING POINT 140°C/284°F.

1. FOLLOW VEHICLE MANUFACTURER'S RECOMMENDATIONS WHEN ADDING BRAKE FLUID. 2. KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products, or other materials may result in brake failure or costly repairs. 3. STORE BRAKE FLUID ONLY IN ITS ORIGINAL CONTAINER. KEEP CONTAINER CLEAN AND TIGHTLY CLOSED TO PREVENT ABSORPTION OF MOISTURE. 4. CAUTION: DO NOT REFILL CONTAINER, AND DO NOT USE FOR OTHER LIQUIDS.

DIRECTIONS: Clean all dirt from around cover on master cylinder before removing. Fill with the level specified by vehicle manufacturer. Replace cover. Check fluid level once a month. TO BLEED SYSTEM: Refer to vehicle owner's manual. Do not re-use brake fluid from bleeding operation. CAUTION: Never touch cylinders or parts with gasoline, kerosene or oil. IMPORTANT: Avoid spilling on brake lining or car finish.

DANGER: Hazard Statements: Keep out of reach of children. Prevent contact with eyes. Avoid contact with skin and clothing. Wash thoroughly after handling. Do not swallow or breathe vapors. Avoid prolonged exposure. Use in well-ventilated areas. IF SPILLED: Flush thoroughly with water for at least 20 minutes. Seek immediate medical attention. IF ON SKIN: Remove contaminated clothing, and wash exposed skin thoroughly with soap and water. If irritation develops and persists, contact a doctor. IF BREATHING IS AFFECTED: Move person into fresh air. IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/hospital.

CHALET PRODUCTS COMPANY
COMMERCIAL, CA 90023 USA
(323) 780-9837
www.chaletproducts.com
info@chaletproducts.com

CHALET GUARANTEES THIS PRODUCT MEETS THE SAME INDUSTRY STANDARDS AS ALL MAJOR BRANDS.

MADE IN U.S.A.
HECHO EN E.E.U.U.
12 FL OZ (0.355L)

SOFIA
DESIGN
STUDIO