



GROUT LOG



Client:

Contract Number:

ID Hole/ Area-

Date:

Who:

GROUT INFORMATION- Circle mix used	
Standard Mix: 25+mpa/ 7 day , 35+mpa/ 28 day.	Modified Mix:
8 litres potable water, 70mls Viscocrete 10, 20kg GP cement	
Note: Mix can be thickened by decreasing water to 7 litres per bag	

GROUTING FIRST FILL		GROUTING SECOND FILL / TOP UP	
Date of grouting	/ /20	Date of grouting	/ /20
Time of grouting	hrs	Time of grouting	hrs
Anticipated volume (L)		Actual volume added:	
Actual volume (L)			
Specific Gravity (Kg)			
Test Taken:			

METHOD OF GROUTING	
<input type="checkbox"/>	Pump grout through piston pump pneumatic mixer or
<input type="checkbox"/>	Pump grout through worm drive directional volume mixer
<input type="checkbox"/>	Pre mix deleivered
<input type="checkbox"/>	Hand mix onsite

Grout volumes per metre- **For Reference**

	20mm Bar	25mm Bar	32mm Bar
50mm Hole	1.7 L	1.5L	1.2L
75mm Hole	4 L	3.9L	3.6L
100mm Hole	7.5 L	7.3L	7L
125mm Hole	13L	12.8L	12.5L